

# DIVELINK®

## Commercial Aquarium Hardwire Two Diver Rack Mount Intercom Model COM-HW-RM-2

### Features:

- Hardwire Two Diver Intercom
- Full Duplex Mitigated Talk and Listen Interface to Public Address System
- Electrical Isolation of Wired Connection to Divers

### SPECIFICATIONS:

<b>Rack Mount Size:</b>	3U Rack Space with handles. 18" Depth, 19.0" Width, 5.25" High.
<b>Weight:</b>	20 lbs approx. with microphone
<b>Audio Interface:</b>	0 dBV Audio Line Levels. XLR I/O. Local Loudspeaker at front panel.
<b>Indicators:</b>	Diver Cable Connected (2); Power ON.
<b>Controls:</b>	External Audio Input Volume to local loudspeaker. Diver Audio Volume to local loudspeaker. Mute Diver to Public Address. Local Microphone Volume to Diver. Push To Talk on local microphone.
<b>Connections:</b>	Front Panel: Hand Held Microphone to Diver with Push To Talk. Rear Panel: 1" waterproof Hardwire Bulkhead Plugs to Two Divers. Audio Input to Divers XLR socket. Audio Output from Divers XLR plug. 120 VAC line cord plug with switch.
<b>Mains Supply:</b>	120 VAC, Cord Supplied
<b>Replaceable Parts:</b>	1 Amp Fuse Slo-Blo MIC-S08 Hand Held Microphone
<b>Internal Power Supply:</b>	Acopian <b>A12MT900FM</b> High reliability High Performance with mold protection.
<b>Electrical Isolation:</b>	Each Diver to Rack 800 V <sub>RMS</sub> Diver Intercom Cable Shield is isolated



Two Diver Hardwire Intercom System



Rear Panel

### This equipment connects with:

CAB-HW-x	Intercom Cables to Diver (-x means length option)
EAR-MIC-NOPTT	Earphone / Volume Control Harness for Diver
MPC-x	Microphone for Diver (-x means Full Face Mask Brand)
DL-SOUNDWEB	Pre-Programmed Interface Module to Public Address

**Applications:** Aquariums